

Dry Ice Blasting Unit

ASCOJET 1208

complete (fully adjustable)

part no. 900960




The **ASCOJET 1208** features a new modern frame design and self-explanatory pictogram. This powerful blasting machine is very easy to use and is particularly suitable for use in industries.

Key benefit of the **ASCOJET 1208** is its lightness (only approx. 48 kg/106.9 lb). Furthermore, the newly integrated grounding roll and the protective grating in the pellet hopper guarantee safe handling during the blasting process.

Powerful and very handy blasting gun:

Thanks to a **quick connect coupling** the gun can be attached to the blasting unit very easily.

Increased security thanks to the **locking pin**, which makes a sudden opening of the locking mechanism of the nozzle impossible.



The **ergonomic gun handle** ensures very easy handling and comfortable operation when blasting over longer periods. The new developed safety button is ideal for left and right-hander.


A **quick exchange system** allows nozzles to be changed within seconds without any tools.

Specifications


Material:	frame and cover sheets made of powder-coated steel
Dimensions (L x W x H) incl. wheels/folded handle:	635 x 491 x 872mm (variable) (25 x 20 x 35 in)
Weight empty:	approx. 62 kg (136.7 lb)
Content of pellet hopper:	approx. 9 kg (19.84 lb)
Working pressure:	0 - 10 bar (0 - 145 psi) (adjustable)
Dry ice consumption:	approx. 20 - 40 kg/h (44 - 88.2 lb/h) (stepless)
Voltage:	230 V, 50/60 Hz, 1 Ph (other voltages on request)
Power consumption:	250 W (0.33 HP) nominal
Connection:	Input: claw coupling 3/4"




ASCOJET 1208: Special features



Powerful and handy blasting gun with quick connect coupling



Highly manoeuvrable




Quick connect coupling at blasting hose




Very lightweight and compact




Integrated holding device for hose



Vertically adjustable handle for easy handling



Integrated grounding wire for more safety



Insulated pellet hopper with 9 kg (19.84 lb) capacity



Control panel for easy overview

ASCOJET 1208: Options

Pos. 001

Lighting kit for dry ice blasting gun

Compact torch
LED light 160 lumen, 160 cm (63 in)
Up to 25 hours battery life

Length: 10.6 cm (4.2 in)
Weight: 120 g (0.35 lb)

OHS
OHP
HP

part no. 4064129



Pos. 002

Tool case OHS/OHP pro

Contains the entire nozzle assortment (excl. gun and standard barrel nozzle, part no. 4063745), fits to the OHS and OHP guns

Consists of 5 nozzles:
part no. 4047228, 4047321, 4047216, 4047222, 4047223

OHS
OHP

part no. 4064567



Pos. 003

Barrel nozzle 707.09/10

Thanks to an inner diameter of only 7 mm (0.28 in) the barrel nozzle has a very economical air consumption but is nevertheless powerful

Outlet opening: approx. \varnothing 10 mm (0.39 in)
Length: 9 cm (3.54 in)
Inner diameter: 7 mm (0.28 in)

OHS
OHP

part no. 4047228



Pos. 004

Barrel nozzle 707.15/12

Thanks to an inner diameter of only 7 mm (0.28 in) the barrel nozzle has a very economical air consumption but is nevertheless powerful

Outlet opening: approx. \varnothing 12 mm (0.47 in)
Length: 15 cm (5.9 in)
Inner diameter: 7 mm (0.28 in)

OHS
OHP

part no. 4047321



Pos. 005

Flat nozzle 709.23/45

Powerful nozzle suitable for blasting large areas

Outlet opening: approx. 45 x 3.5 mm (1.77 x 0.14 in)
Length: 23 cm (9 in)
Inner diameter: 9 mm (0.35 in)

OHS
OHP

part no. 4047216



Pos. 006

Angled nozzle 708.28/10/45°

A powerful nozzle for confined spaces with very low air consumption

Outlet opening: approx. \varnothing 10 mm (0.39 in)
Length: 28 cm (11 in)
Inner diameter: 8 mm (0.31 in)

OHS
OHP

part no. 4047222



ASCOJET 1208: Options

Pos. 007

Angled nozzle 708.25/10/75°

A powerful nozzle for confined spaces with very low air consumption

Outlet opening: approx. Ø 10 mm (0.39 in)

Length: 25 cm (9.84 in)

Inner diameter: 8 mm (0.31 in)

OHS
OHP

part no. 407223



Pos. 008

Tool case OHS/OHP pro empty

Empty tool case with matching insert

OHS
OHP

part no. 4064570



Pos. 009

Pellet cutter OHS

For sensitive blasting applications

With safety quick connect coupling, 2.5 m (8.2 ft) hose and control cable, grounded

OHS

part no. 4047026



Pos. 010

Protective sleeve for one hose system 165 mm (6.5 in)

To protect the control cable and blasting hose from dirt and damages

Available in meters

OHS
OHP

part no. 4047265



Pos. 011

Protective hood for ASCOJET 1208

The newly developed hood for our blasting equipment protects the control elements from contamination. The transparent cover can be opened for easy view on and access to the operation elements. For cleaning the hood can easily be taken off.

part no. 4064528



Pos. 012

Spare parts kit ASCOJET 1208

Containing the most important parts to ensure quick reaction for continuous operation

part no. 4064527



ASCOJET 1208: Options

Pos. 013

Compressed air hose 7.5 m (24.6 ft) / ID 25 mm (1 in)

part no. 4045955

Connecting hose between air compressor and dry ice blasting machine, incl. claw coupling and safety ring for fast and easy connection / disconnection
Material: Fabric hose / metal
Dimension: 7.5 m (24.6 ft)
Weight: 2.4 kg (5.29 lb)



Blasting gun OHS6

part no. 4063745

Standard for the ASCOJET1208
Length: 26 cm (10.24 in)
Weight: 1.0 kg (2.2 lb)
Blasting pressure: 0 - 10 bar (0 - 145 psi)

OHS



High performance barrel nozzle 707.15/12

part no. 4047321

Standard for the blasting gun OHS
Powerful nozzle with low air consumption
Outlet opening: approx. Ø 12 mm (0.47 in)
Length: 15 cm (5.9 in)
Inner diameter: 7 mm (0.28 in)

OHS



Hose assembly 5 m for OHS gun ID16 mm (196.85 in ID 0.63 in)

part no. 4047104

Standard for the ASCOJET 1208, can also be used as an extension of the hose assembly
incl. control cable, grounded

OHS

