

Data Sheet

torbo[®] **SoftLine S**



Small but powerful

The SoftLine machines are the smallest devices for the simple, effective and gentle cleaning of monuments and facades. They don't need an extra air dryer, no extra water hose to the nozzle and no heavy or expensive nozzle. Thanks to the control system, the blasting media mixture (80% blasting abrasive and 20% water) and extra water is metered out irrespective of compressed air, so that you can adjust the parameters independently of each other.

Technical Data	SoftLine S
Vessel size	60 l
Water tank	---
Hose reel	---
Compressor	---
Blasting media consumption (min. – max.)	0,24 - 2,40 l/min / 0,06 – 0,63 gpm
Water consumption	0,06 – 0,60 l/min / 0,02 – 0,16 gpm
Compressed air connection	$\frac{3}{4}$ inch 2,8 – 4,0 m ³ /min 4 – 10 bar
Water connection (min. – max.)	0,2 – 12,0 bar / 0 – 170 PSI
Blasting hose connection	19 mm / $\frac{3}{4}$ inch
Power supply	12 volt / 4 watt
Dimensions (H x W x D)	570 x 520 x 990 mm / 22 x 20 x 39 inch
Tade weight, approx.	130 kg / 290 lbs.
Perm. total weight, approx.	500 kg / 1102 lbs.

Status: 2017 | All data without guarantee